

# Specification Sheet

Model # 70RA08



## MISCO®

### Key Features:

- 2.7" (70mm), 8 ohm
- Voice Range, 500 milliwatts
- Alnico magnet, paper cone;

## Product Specifications & Parameters

### Primary Specifications

Speakers Environment	Indoor
RoHS Compliant	No

### Technical Specifications

		Units of Measure
Nominal Basket Diameter	2.7	inch
	70.0	mm
Rated Impedance	8	ohms
Rated Power	0.0	Watts
Program Power	1	Watts
Frequency Range	280 - 3200	Hz
Sensitivity (2.83 V input measured at 1 Meter)	85	dB SPL
Voice Coil Diameter	0.6 / 15.2	inch / mm
Magnet Weight	0.4 / 10	oz / gr
Transformer		


### Small Signal Parameters

		Units of Measure
Resonant Frequency (fo)	280	Hz
D.C. Resistance (Re)	7.4	ohms
Mechanical Q (Qms)	5.5	
Electrical Q (Qes)	7.74	
Total Q (Qts)	3.21	
Compliance Equivalent Volume (Vas)		ltr
BL Product (BL)		T-M
Maximum Linear Excursion (Xmax)		mm
Surface Area of Cone (Sd)		cm <sup>2</sup>
Moving Mass (Mmd)		g

### Material Descriptions

Basket	Stamped Steel
Terminal Size	.12 X .02
Magnet	Alnico
Voice Coil Wire	Copper
Voice Coil Form	Paper
Cone	Paper
Cone Edge	Paper
Dust Cap	Paper

## Sensitivity / Frequency



## Drawing

ID	Description	Measurements	Tolerance
Od	Outside Diameter	2.8 in.	+/- 0.020"
CD	Cutout Diameter	2.5 in.	+/- 0.020"
MG	Magnet Diameter	0.87 in.	+/- 0.050"
HD	Hole Diameter	in.	+/- 0.010"
MD	Mounting Diameter	in.	+/- 0.010"
ID	Internal Depth	0.8 in.	+/- 0.025"
FT	Flange Thickness	0.1 in.	+/- 0.050"
NW	Net Weight	47.0 g	

