

The DC3S 3" voice range speaker provides clear and intelligible communications for systems in need of a high sensitivity solution with an impedance of 8 ohms. A water-resistant cone treatment ensures this model holds up in a variety of indoor enclosures, and a sturdy steel frame and powerful ferrite magnet give this model strong, consistent, and long-lasting performance.

- Voice range speaker
- 3" (77 mm) steel basket diameter
- 6 watts, 8 ohm, 92 dB SPL
- 0.6" copper voice coil, aluminum former
- 2.35 oz. ferrite magnet, water-resistant paper cone



Primary Specifications

Size, Nominal (inch & mm)	3" (77 mm)
Rated Impedance (Ω)	8
Sensitivity (dB SPL) ¹	92
Frequency Range (Hz)	250 - 8,000
Resonant Frequency (Fs) (Hz) +/- 15%	32

More Specifications

Application	Indoor, Voice Communications
RoHS Compliant	No
Program Power (W)	12

Small Signal Parameters

Nominal Impedance (Z) (Ω)	8
Resonant Frequency (Fs) (Hz) +/- 15%	32

Material Descriptions

Basket Type	Stamped steel
Terminal Size (mm)	4.8 x 0.5
Voice Coil Diameter (mm)	15.2
Voice Coil Wire Material	Copper
Voice Coil Former Material	Aluminum
Magnet Material	Ferrite
Magnet Weight (g)	67
Cone Body Material	Treated paper
Net Weight (kg)	0.2

